

Material Safety Data Sheet

Issue Date : July 2006

Issued by : EnviroOil

Page 1 of 4

Product Names(s)

EnviroLube HVI 46
EnviroLube HVI 68

Company Details

Company Name EnviroOil Co. of Australia Pty Ltd (ABN 92 108 255 410)
Address Suite 18, 12 Tryon Rd
Lindfield, NSW 2070
Emergency Tel. (02) 9416 5418 ; 24 hr
Product and MSDS Info: (02) 9416 0628

Product Identification

Product Name ENVIROLUBE HVI 46, ENVIROLUBE HVI 68
Product Use HYDRAULIC OIL

Hazard Identification

Hazard Classification NON-HAZRADOUS SUBSTANCE
NON-DANGEROUS GOOD
Risk Phrases Not Applicable
Safety Phrases Not Applicable
Hazard classification according to the NOHSC
Dangerous goods classification according to ADG Code

Physical & Chemical Properties

Appearance Liquid
Colour Amber
Boiling point > 316°C
Melting point NA
Flash point (PMCC) > 180°C (ASTM D-93)
Flammability NE
Auto Flammability NE
Solubility in Water Negligible

pH NA
Explosive Properties NA
Oxidizing Properties NA
Vapour Pressure < 0.1 (mmHg @ 20°C)
Vapour Density > 2.0

Material Safety Data Sheet

Issue Date : July 2006

Issued by : EnviroOil

Page 2 of 4

Product Names(s) **EnviroLube HVI 46**
EnviroLube HVI 68

Evaporation Rate NE
Relative Density 0.87 (@15°C)
Partition Coefficient > 3.5
Viscosity HVI 46 typically 46 cSt (@ 40°C)
HVI 68 typically 68 cSt (@ 40°C)
Pour Point < -10 °C
Freezing Point NE

NA=NOT APPLICABLE

NE=NOT ESTABLISHED

Ingredients

Composition Contains Petroleum distillates and additives
Ingredients determined not to be hazardous
CAS not required

Ingredients	<u>Name</u>	<u>CAS</u>	<u>Proportion</u>
	Ingredient determined not to be hazardous	Not Required	100%

First Aid Measures

Swallowed Do not induce vomiting. As a precaution, rinse mouth with water. Seek medical attention.

Eye Flush eyes immediately with fresh water for several minutes while holding the eyelids open.

Skin Wash skin thoroughly with soap and water.

Inhaled If respiratory irritation or any signs or symptoms as described in this MSDS occur, move the person to fresh air. If any of these effects continue, see a doctor.

Advice to Doctor Treat symptomatically

Fire Fighting Measures

Extinguishing media Carbon dioxide, dry chemical, foam or water fog
Do NOT use water jets. Cool containers exposed to fire with water fog.

Specific Hazards Combustible C2 liquid. Fire-exposed container may rupture/explode

Combustion Products May emit toxic or irritating fumes, including oxides of carbon

Material Safety Data Sheet

Issue Date : July 2006

Issued by : EnviroOil

Page 3 of 4

Product Names(s)

EnviroLube HVI 46
EnviroLube HVI 68

Precautions

Self contained breathing apparatus (SCBA) and full protective clothing

Accidental Release Measures

Spills

Wear protective equipment to prevent skin and eye exposure And inhalation of vapours/mists. Work upwind or increase ventilation. Contain any spillage using absorbent soil, sand or any other inert material and prevent runoff to drains and waterways. Collect, seal and label drums for disposal. Wash down with detergent and excess water.

Disposal

Refer to State Land Waste Management Authority.
Normally suitable for incineration by approved agent.

New or used mineral oils, or solvent must not be allowed to enter the ground, ground water, water courses, sewers or drainage systems. Dispose of waste according to federal, E.P.A. and state regulations. Assure conformity with all applicable regulations.

Storage and Transport

Transport

Not classified as dangerous by the criteria of the ADG Code for transport by road or rail.

UN Number: N/A

Dangerous Good Class: N/A

Proper Shipping Name: N/A

Hazchem Code (Aus/NZ): N/A

Storage Regulations

Combustible C2 liquid for storage and handling purposes. Store in a well ventilated area. Store away from halogens, strong acids, alkalis, oxidizing agents and foodstuffs. Reference should be made to AS1940-“The Storage and Handling of Flammable and Combustible Liquids”

Stability and Reactivity

Stability

Stable under normal conditions

Hazardous Polymerisation

Will not occur

Materials to avoid

Strong oxidising agents

Hazardous Decomposition

Thermal decomposition/combustion produces noxious fumes including carbon dioxide.

Conditions to avoid

Heat, direct sunlight, open flames, oxidising agents or other sources of ignition

Material Safety Data Sheet

Issue Date : July 2006

Issued by : EnviroOil

Page 4 of 4

Product Names(s)

EnviroLube HVI 46
EnviroLube HVI 68

Personal Protection

Eye Protection

Safety glasses

Clothing

Overalls, safety shoes and gloves.

Work/Hygienic Practices

Avoid skin and eye contact and inhalation of vapours. Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Flammability

Classified as Class C2 Combustible liquid

Fire Hazards

See Safe Handling Information.

Regulatory Information

Poisons Schedule

Not Schedules

AICS

All components in this product are listed on AICS (Australian Inventory of Chemical Substances).

...End of MSDS....