



# AGRITRANS 15W-30

## Application

EnviroLube AgriTrans 15W-30 is a universal transmission fluid for use in wet brakes, hydraulics, PTO's and a wide variety of agricultural, construction and industrial transmissions.

It is particularly well suited for reducing wet brake and power take-off (PTO) chatter and is outstanding for use as a hydraulic fluid in systems where and SAE 15W or 30 grade engine oil is recommended.

## Availability

Packs 20L, 205L

## Features

EnviroLube AgriTrans 15W-30 is premium universal tractor transmission oil (UTTO). It offers rationalisation on the farm, while still providing excellent protection in all components from wear, corrosion, oil consumption and equipment noise and chatter.

### *Contains chatter suppression agents*

It is formulated from double refined base oils which substantially reduce environmental impacts compared to conventional fluids. Double refined base oils impart superior oxidation stability to maintain product performance in prolonged operation and also provide excellent low temperature properties for operation in cooler climates.

In addition, the additive chemistry has enhanced friction properties to minimise wet brake and PTO chatter and is approved by Ford New Holland, John Deere, Massey and ZF.

## Benefits

- ✓ Simplifies oil inventory and servicing, reducing cost and reduce risk associated with mis-application
- ✓ Anti-Squawk chemistry to minimises wet brake chatter
- ✓ High thermal stability for durability in heavy duty applications
- ✓ Outstanding wear protection to prolong component life.
- ✓ Protects against corrosion from accumulation of moisture and acids
- ✓ Manufactured in an ISO 9002 certified facility to ensure strict quality control and best practice production methods.
- ✓ Double refined base stocks conserve vital petroleum resources



# AGRITRANS 15W-30

## Safety

Your safety is important to EnviroOil. This material is classified as non-hazardous according to Worksafe Australia. However, it is recommended that the handling instructions in the Material Safety Data Sheet be followed to avoid risk of injury or irritation from exposure.

## Specifications

EnviroLube AgriTrans 15W-30 is recommended where the following performance levels are specified

Specifications	
SAE	15W-30
API	GL-4
Ford/New Holland	FNHA-2-C-201 (M2C86-B, C, M2C134-B, C)
John Deere	J20C
Case	MS 1206, 1207, 1209
Massey	M1135, M1143, M1141 (M1127A)

### Notes

1. The specification FNHA-2-C-201 replaces M2C134-D
2. The specification M1141 replaces M1127A, M1127B, M1129 and M1110
3. Do not use EnviroLube AgriTrans in
  - o passenger vehicle automatic transmissions
  - o 2 or 4 stroke petrol or diesel engines
  - o hypoid differentials specifying API GL-5

## Typical Characteristics

Characteristic	Method	Units	Typical Value	Benefit
Viscosity Grade	SAE	Engine Gear	15W-30 80W-85	Provides a wide range of operating viscosity for protection in all climates. Shear stable product means viscosity is maintained for life of lubricant
Density @ 15.6C	IP160	g/cm <sup>3</sup>	0.87	
Viscosity at 100°C	ASTM D445	cSt	9.4	
Viscosity at 40°C	ASTM D445	cSt	65	
Viscosity Index	ASTM D2270		124	
Pour Point	ASTM D97	°C	-35	Cold climate operation
Sulphated Ash	ASTM D84	%wt	1.4	High additive treat for cleanliness, friction control, corrosion prevention and wear protection

Values provided are typical and do not constitute a specification