

ENVIROLUBE

Chain Saw Oil

CHAINBAR 100

Application

EnviroLube ChainBar 100 lubricates the chain, sprocket and guide bar of chainsaws during arduous cutting operations. It is suitable for almost all chainsaws with an automatic oiling system.

Availability

Packs 20L, 205L, 1000L


Features

EnviroLube ChainBar 100 is fortified with selected additives, designed to minimise fling off, maximise penetration, reduce sap sticking, prevent wear and reduce friction during cutting operations. It also helps to minimise corrosion of idle equipment.

Benefits

- ✓ Tackifier agents reduce fling off and product waste
- ✓ Anti-wear additives extend the life of the chain
- ✓ Lubricity agents fights sap sticking
- ✓ Anti-corrosive additives minimise rust formation when machinery is idle
- ✓ Double refined base oils conserve vital petroleum resources

| Intended for lubrication of chainsaw guides |

**Chain Saw Oil****CHAINBAR 100****Safety**

Your safety is important to EnviroOil. This material is classified as non-hazardous according to Worksafe Australia. However, it is recommended that the handling instructions in the Material Safety Data Sheet be followed to avoid risk of injury or irritation from exposure.

Specifications

EnviroLube ChainBar 100 is suitable for almost all chainsaws with automatic oiling systems.

Typical Characteristics

| Characteristic | Method | Units | Typical Value | Benefit |
|-------------------|------------|-------------------|---------------|---|
| Viscosity Grade | ISO | | 100 | Covers a broad range operating conditions |
| Density @ 15.6C | IP160 | g/cm ³ | 0.88 | |
| Viscosity at 40°C | ASTM D445 | cSt | 99 | |
| Viscosity Index | ASTM D2270 | | 107 | |
| Pour Point | ASTM D97 | °C | -12 | |

Values provided are typical and do not constitute a specification