

# Material Safety Data Sheet

Page: 1 of 4

Infosafe No. LPUV3 Issue Date : September 2005 ISSUED by ENVIROOI

Product Name : ENVIROLUBE HD-J 15W-40

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

**Product Name** ENVIROLUBE HD-J 15W-40  
**Company Name** Enviro Oil Co of Australia  
**Address** 12 Tryon Road Lindfield  
NSW 2070 Australia  
**Emergency Tel.** 02 9416 5418; 24hr  
**Telephone/Fax Number** Tel: 02 9416 0628 Fax: 02 9416 2583  
**Recommended Use** Diesel engine oil.

## 2. HAZARDS IDENTIFICATION

**Hazard Classification** NON-HAZARDOUS SUBSTANCE.  
NON-DANGEROUS GOODS.  
Hazard classification according to the criteria of NOHSC.  
Dangerous goods classification according to the Australia Dangerous Goods Code.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Distillates (petroleum), Solvent Dewaxed, Heavy Paraffinic	64742-65-0	60-100 %
	Ingredients determined not to be hazardous		Balance to 100%

## 4. FIRST AID MEASURES

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. If symptoms develop seek medical attention.  
**Ingestion** Do NOT induce vomiting. Wash out mouth with water. Seek medical attention.  
**Skin** Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. If symptoms develop seek medical attention.  
**Eye** If contact with the eye(s) occurs, wash with copious amounts of water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If symptoms persist seek medical attention.  
**First Aid Facilities** Eye wash and normal washroom facilities.  
**Advice to Doctor** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media** Use carbon dioxide, dry chemical or foam.  
**Hazards from Combustion Products** Under fire conditions this product may emit toxic and/or irritating fumes including zinc, calcium, sulphur and oxides of carbon.  
**Hazchem Code** None Allocated  
**Precautions in connection with Fire** Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency Procedures** Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

# Material Safety Data Sheet

Infosafe No.	LPUV3	Issue Date : September 2005	ISSUED by ENVIROOI
Product Name :	ENVIROLUBE HD-J 15W-40		

---

## 7. HANDLING AND STORAGE

---

<b>Precautions for Safe Handling</b>	Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with this product, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. Washing hands prior to eating, drinking, smoking or using toilet facilities.
<b>Conditions for Safe Storage</b>	Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

<b>National Exposure Standards</b>	No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m <sup>3</sup> . As with all chemicals, exposure should be kept to the lowest possible levels.
<b>Biological Limit Values</b>	No biological limit allocated.
<b>Engineering Controls</b>	Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.
<b>Respiratory Protection</b>	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
<b>Eye Protection</b>	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
<b>Hand Protection</b>	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
<b>Body Protection</b>	Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	Amber liquid.
<b>Odour</b>	Not available.
<b>Melting Point</b>	Not applicable.
<b>Boiling Point</b>	Not available.
<b>Solubility in Water</b>	Insoluble.

# Material Safety Data Sheet

Page: 3 of 4

Infosafe No.	LPUV3	Issue Date : September 2005	ISSUED by ENVIROOI
--------------	-------	-----------------------------	--------------------

Product Name : **ENVIROLUBE HD-J 15W-40**

---

<b>Specific Gravity</b>	0.891 (15°C)
<b>pH Value</b>	Not available.
<b>Vapour Pressure</b>	Not available.
<b>Vapour Density (Air=1)</b>	Not available.
<b>Viscosity</b>	113 cSt (40°C) 15 cSt (100°C)
<b>Flash Point</b>	180°C (CC)
<b>Auto-Ignition Temperature</b>	Not available.
<b>Flammable Limits - Lower</b>	Not available.
<b>Flammable Limits - Upper</b>	Not available.

---

## 10. STABILITY AND REACTIVITY

---

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling.
<b>Conditions to Avoid</b>	Heat, direct sunlight, open flames or other sources of ignition.
<b>Incompatible Materials</b>	Oxidising agents, acids and halogens.
<b>Hazardous Decomposition Products</b>	Thermal decomposition and combustion produce noxious fumes containing oxides of carbon and aldehydes.
<b>Hazardous Reactions</b>	Hazardous polymerisation will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

<b>Inhalation</b>	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
<b>Ingestion</b>	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
<b>Skin</b>	May cause redness, itching and irritation.
<b>Eye</b>	May cause eye irritation, tearing, stinging, blurred vision, and redness.
<b>Chronic Effects</b>	Prolonged or repeated contact may result in skin irritation leading to dermatitis. Repeated exposure to vapour or mist at concentrations in air that exceed exposure standards can cause respiratory irritation, discomfort or other pulmonary effects.

---

## 12. ECOLOGICAL INFORMATION

---

<b>Ecotoxicity</b>	No data is available for this material.
<b>Persistence / Degradability</b>	No data is available for this material.
<b>Mobility</b>	No data is available for this material.
<b>Environ. Protection</b>	Prevent material from entering the environment.

---

## 13. DISPOSAL CONSIDERATIONS

---

<b>Disposal Considerations</b>	Dispose of waste according to federal, EPA and state regulations.
--------------------------------	---

---

## 14. TRANSPORT INFORMATION

---

<b>Transport Information</b>	Not classified as Dangerous Goods, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
<b>U.N. Number</b>	None Allocated
<b>Proper Shipping Name</b>	None Allocated
<b>DG Class</b>	None Allocated
<b>Hazchem Code</b>	None Allocated

# Material Safety Data Sheet

Page: 4 of 4

Infosafe No.	LPUV3	Issue Date : September 2005	ISSUED by ENVIROOI
--------------	-------	-----------------------------	--------------------

Product Name : **ENVIROLUBE HD-J 15W-40**

---

**Packing Group**            None Allocated

---

## 15. REGULATORY INFORMATION

---

**Poisons Schedule**        Not Scheduled

---

## 16. OTHER INFORMATION

---

**Date of preparation**        MSDS created: 2005.

**or last revision of**

**MSDS**

...End Of MSDS...