

## PRODUCT RANGE 2006

### Heavy Transport, Earthmoving, Construction & Mining

#### EnviroLube HD Ultra 15W-40



EnviroLube HD Ultra is a superior quality diesel engine oil formulated to extend drain intervals and increase engine durability in severe service.

US, European & Japanese Medium to Heavy Duty Diesel

**20L,205L, 1000L**

API CI-4 Plus  
ACEA E7  
Global DHD-1

#### EnviroLube HD Diesel 15W-40



EnviroLube HD Ultra is a superior quality diesel engine oil formulated to extend drain intervals and increase engine durability in severe service.

US, European & Japanese Medium to Heavy Duty Diesel

**20L,205L, 1000L**

API CI-4  
ACEA E7  
Global DHD-1

#### EnviroLube HD-J 15W-40



EnviroLube HD-J is a high performance, high detergent oil designed specifically to meet the requirements of modern Japanese engines. EnviroLube HD-J maximises engine cleanliness and minimises bore polishing, glazing and reduces ring wear.

Japanese Heavy Duty Diesel

**20L, 205L**

Jaso DH-1  
API CF  
ACEA E2

#### EnviroLube HD-X 15W-40



EnviroLube HD-X is suitable for US heavy duty equipment (on or off highway), diesel 4WD and light commercial vehicles. For mixed fleets the prime recommendation is EnviroLube HD Diesel 15W-40.

US Heavy Duty Diesel

**205L**

API CH-4

#### EnviroLube PowerTO 410, 430, 450



EnviroLube PowerTO is a range of high performance transmission fluids for use on or off road where CAT TO-4 type fluids are required. Also suitable for certain Komatsu, ZF, Meritor, Allison and Eaton transmissions.

Heavy Duty Transmissions

**20L, 205L, 1000L**

CAT TO-4  
Allison C4  
ZF TE-ML 03

#### EnviroLube FD 85W-140, 80W-90



EnviroLube FD 80W-90 and FD 85W-140 are premium hypoid differential oil for use on or off road in high torque applications.

Differentials and Final Drives

**20L, 205L**

API GL-5

#### EnviroLube HLP-HM 32, 46, 68



EnviroLube HLP-HM is a series of formulated hydraulic oils designed to minimise corrosion, oxidation, foaming and machinery wear for use in highly stressed gear, vane and piston type hydraulic systems.

Hydraulic systems where high levels of anti-wear performance are needed

**20L, 205L, 1000L**

Denison HF-0  
DIN 51524, Part 2  
ISO 6743/4  
Vickers I-286-S,  
Vickers M-2950-S

#### EnviroLube HD Coolant 50



EnviroLube HD Coolant 50 is a premixed long life engine coolant suitable for protecting the cooling systems of engines operating in heavy duty cycle conditions with both ferrous and aluminium construction. Compatible with Caterpillar Conditioner and Fleetguard DCA4 Supplemental Coolant Additives.

Diesel trucks, buses, marine, locomotive and static engines

**205L, 1000L**

See PDS for full reference

## PRODUCT RANGE 2006

### Agriculture

#### EnviroLube Agri 20W-40



EnviroLube Agri is a universal farm oil suitable for a wide range of applications around the farm. It is designed to protect engines, transmissions, wet brakes, hydraulics, front axels, power takeoffs, hydrostatics and power steering.

Tractor Engines & Transmissions, PTO, Wet Brakes, Hydraulics

20L, 205L

API CF-4 (CH-4 Soot control)  
API GL-4 (Gear)

#### EnviroLube AgriTrans 15W-30



EnviroLube Agritrans is designed as a universal transmission oil for use in a wide variety of tractors requiring a common oil for transmission, differential and final drives, hydraulics, wet clutches and wet brakes. Contains chatter suppression additives.

Most tractor transmissions, wet brakes and hydraulics.

20L, 205L

API GL-4  
MF 1135, 1141, 1143  
JD 20C  
Case 1206/07/09

#### EnviroLube ChainBar 100



EnviroLube ChainBar 100 lubricates the chain, sprocket and guide bar of chainsaws during arduous cutting operations. It is suitable for almost all chainsaws with an automatic oiling system. Contains tackifier.

Timber Cutting

20L, 205L

### Ancillary Products

**EnviroLube XP 15W-40 & 10W-30** Passenger car and light duty diesel engine oils

**EnviroLube DX III** Automatic transmission fluid formulated to the Dexron® specification. Available in mineral and synthetic versions

**EnviroLube HVI 46 & 68** Shear stable high viscosity index hydraulic fluids

**EnviroLube LSD 90** Passenger & light commercial limited slip differentials

**EnviroLube MTF 75W-90** Manual transmission and rear axle fluid, formulated to improve gearshift across a wide temperature range

### Grease Characteristic Chart

Characteristic	EnviroLube LCX 2	EnviroLube LCX-M 2
Load/Shock	★★	★★★
Water Washout	★★	★★
High Speed Bearings	★★	★
Pumpability	★	★
Vibration/Leakage	★★★	★★★

For further information please go to our website [www.envirooil.com.au](http://www.envirooil.com.au), call EnviroLube Technical Support on 1300 723 190 or call our office on 02 9416 0628.